

### **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listings, of claims in the application.

#### **Listing of Claims:**

1. (Currently Amended) Packaging for of a detonating cord examined by the method of claim 8, in particular for firing wherein the detonating chord is used to ignite a shaped charge perforators perforator in a perforating gun guns in the oil and natural gas industry[[,]]; and characterised in that wherein the detonating cord is wound in a single plane as a flat spiral; and wherein a result of the X-ray examination does not reveal any defect which would lead to failure of the detonating cord.

2. (Currently Amended) The Ppackaging according to claim 1, characterised in that wherein the detonating cord is wound on a base plate.

3. (Currently Amended) The Ppackaging according to claim 1, characterised in that wherein at least two individual laps of the flat spiral are spaced from one another.

4. (Currently Amended) The Ppackaging according to claim 3, characterised in that a wherein the space between the at least two individual laps of the flat spiral is produced by a spacing cord extending in parallel, wherein the thickness of the spacing cord corresponds to the necessary space.

5. (Currently Amended) ~~The P~~packaging according to claim 1, characterised in that wherein a last lap of the flat spiral is passed perpendicularly over the rest of the flat-wound spiral.

6. (Currently Amended) ~~The P~~packaging according to claim 2, characterised in that wherein the base plate of the packaging ~~consists of~~comprises at least one of paperboard, wood ~~or~~ and polystyrene.

7. (Currently Amended) ~~The P~~packaging according to claim 1, characterised in that wherein the detonating cord is sealed in a vacuum bag~~[[,]]~~; which is and wherein the vacuum bag is attached to the base plate-(2).

8. (Currently Amended) A method of examining a packaging of a detonating cord, in packaging, ~~characterised in that~~comprising: subjecting the detonating cord is subjected to X-ray examination in its packaging prior to shipping.

9. (Currently Amended) The method according to claim 8, ~~characterised in that~~ wherein the detonating cord is wound in a single plane as a flat spiral.

10. (New) The method according to claim 8, further comprising: shipping the packaging containing detonating cord when a result of the X-ray examination does not reveal any defect which would lead to failure of the detonating cord.

11. (New) The method according to claim 9, wherein the detonating cord is of a type that ignites a shaped charge perforator in a perforating gun.

12. (New) The method according to claim 11, wherein the shaped charge perforator and the perforating gun are of types used in the oil and natural gas industry.

13. (New) The method according to claim 9, wherein the detonating cord is wound on a base plate.

14. (New) The method according to claim 13, wherein the base plate comprises at least one of paperboard, wood and polystyrene.

15. (New) The method according to claim 9, wherein at least two individual laps of the flat spiral are spaced from one another.

16. (New) The method according to claim 15, wherein the space between the at least two individual laps of the flat spiral is produced by a spacing cord extending in parallel to the detonating cord; and wherein the thickness of the spacing cord corresponds to the space.

17. (New) The method according to claim 9, wherein a last lap of the flat spiral is passed perpendicularly over the rest of the flat spiral.

18. (New) The method according to claim 9, wherein the detonating cord is sealed in a vacuum bag; and wherein the vacuum bag is attached to a base plate.